



# GNSS SMART ANTENNA FOR MACHINE CONTROL SYSTEMS



The A326 is an all-new multi-GNSS, multi-frequency smart antenna. Showcasing fast start-up and reacquisition times, and an easy-to-see status indicator for power, GNSS, and Bluetooth. The durable enclosure houses the high precision antenna element and GNSS receiver. Resulting in the A326 smart antenna being ideal for a variety of applications. The available multiple communication ports, such as Bluetooth, Wi-Fi, dual-Serial, and CAN options make the A326 compatible with almost any interface. The easy-to-use WebUI allows the user to wirelessly monitor and configure the A326 with any Wi-Fi capable device, making the A326 one of the most versatile GNSS smart antennas in the world.

### Athena™ RTK

The A326 GNSS Smart Antenna uses Hemisphere GNSS' next-generation Athena RTK engine. Athena offers world class performance in the areas of initialization time, robustness in very difficult operating environments, superior performance over long RTK baselines, and exceptional reliability in scintillation conditions.

### Atlas® GNSS Global Corrections

A326 is Atlas ready, and capable of receiving corrections from Hemisphere's Atlas Global Correction Service.

A326 is supported by our easy-to-use Atlas Portal ([www.atlasgnss.com](http://www.atlasgnss.com)), which empowers you to update firmware and enable functionality, including Atlas subscriptions for accuracies from meter to sub decimeter levels.

### Key Features

- Atlas GNSS Global Correction Service
- Athena RTK engine
- Powerful WebUI accessed via Wi-Fi
- Internal memory for data logging, download, and upload
- Durable enclosure is proven to withstand aggressive environments

## GNSS Receiver Specifications

**Receiver Type:** GNSS Position RTK Receiver  
**Signals Received:** GPS, GLONASS, Galileo, BeiDou, QZSS  
**Channels:** 572 / 488  
**GPS Sensitivity:** -142 dBm  
**SBAS Tracking:** 3-channel, parallel tracking  
**Update Rate:** 10 Hz standard, 20 Hz optional (with subscription)

### Timing (1 PPS)

**Accuracy:** 20 ns  
**Cold Start:** < 60 s typical (no almanac, ephemeris, position, or RTC)

**Warm Start:** < 30 s typical (almanac and RTC)  
**Hot Start:** < 10 s typical (almanac, ephemeris, position, and RTC)

**Maximum Speed:** 1,850 kph (999 kts)  
**Maximum Altitude:** 18,000 m (59,055 ft)

### Accuracy

Positioning:	RMS (67%)	2DRMS (95%)
<b>Autonomous, no SA:</b> <sup>1</sup>	1.2 m	2.5 m
<b>SBAS:</b> <sup>1</sup>	0.3 m	0.6 m
<b>Atlas:</b> <sup>1,3</sup>	0.08 m	0.16 m
<b>RTK:</b> <sup>1,2</sup>	8 mm + 1 ppm	15 mm + 2 ppm

## L-Band Receiver Specifications

**Receiver Type:** Single Channel  
**Channels:** 1530 to 1560 MHz  
**Sensitivity:** -130 dBm  
**Channel Spacing:** 5 kHz  
**Satellite Selection:** Manual or Automatic  
**Reacquisition Time:** 15 sec (typical)

### Communications

**Ports:** 2 full-duplex RS-232, CAN  
**Interface Level:** Atlas GNSS (WebUI)  
**Baud Rates:** 4800 - 115200  
**Correction I/O Protocol:** Hemisphere GNSS proprietary ROX format, RTCM v2.3, RTCM v3.2, CMR<sup>5</sup>, CMR+<sup>5</sup>

**Data I/O Protocol:** NMEA 0183, NMEA 2000, Hemisphere GNSS binary, Bluetooth 2.0 (Class 2), Wi-Fi  
**Timing Output:** 1 PPS, CMOS, active high, rising edge sync, 10 kΩ, 10 pF load

### Event Marker

**Input:** CMOS, active low, falling edge sync, 10 kΩ, 10 pF load

### Power

**Input Voltage:** 7-32 VDC  
**Power Consumption:** 4.5 W nominal (L1/L2 GPS/GLONASS/BeiDou, L-band)  
**Current Consumption:** 0.38 A nominal (L1/L2 GPS/GLONASS/BeiDou, L-band)  
**Power Isolation:** No  
**Reverse Polarity Protection:** Yes

### Environmental

**Operating Temperature:** -40°C to +70°C (-40°F to +158°F)  
**Storage Temperature:** -40°C to +85°C (-40°F to +185°F)  
**Humidity:** 95% non-condensing  
**Mechanical Shock:** 50G, 11ms half sine pulse (MIL-STD-810G w/Change 1 Method 516.7 Procedure 1)  
**Vibration:** 7.7Grms (MIL-STD-810G w/Change 1 Method 514.7 Category 24)  
**EMC:** CE (ISO14982/EN13309/ISO13766/IEC60945), Radio Equipment Directive 2014/53/EU, E-Mark, RCM  
**Enclosure:** IP67

### Mechanical

**Dimensions:** 15.8 L x 15.8 W x 7.9 H (cm)  
6.2 L x 6.2 W x 3.2 H (in)  
**Weight:** < 1.15 kg (< 2.53 lbs)  
**Status Indications (LED):** Power, GNSS Status, Bluetooth, Wi-Fi  
**Power/Data Connector:** 12-pin male  
**Antenna Mounting:** 1-14 UNS-2A female adapter, 5/8-11 UNC 2B adapter, flat mount available

1. Depends on multipath environment, number of satellites in view, satellite geometry, and ionospheric activity
2. Depends also on baseline length
3. Requires a subscription from Hemisphere GNSS
4. With L5 option 5 With B3 option
5. CMR and CMR+ do not cover proprietary messages outside of the typical standard



## Hemisphere GNSS

8515 E. Anderson Drive  
Scottsdale, AZ 85255, USA

Phone: +1 (480) 348-6380  
Toll-Free: +1 (855) 203-1770  
Fax: +1 (480) 270-5070

precision@hgns.com  
www.hgns.com